


High Power

RadioRouter module for MULTICAL® 602

DATA SHEET

- Automatic radio reading of MULTICAL® 602
- High transmission power
- Built-in router functionality
- Autodetection of radio frequency on two channels
- Built-in radio antenna and external antenna connection
- Two extra pulse inputs for connection of water and electricity meters
- Plug-and-play
- Supports leakage and bursting alarms
- Data from the meter is read in as little as one second



Application

The High Power RadioRouter module is mounted in a MULTICAL® 602 and functions as a router unit in a radio network. In addition, the module functions as an ordinary radio module and can be read via hand-held terminal.

The module can be installed in a MULTICAL® 602 without configuration and is ready for communication in less than 30 seconds after mounting.

The reading system then determines which data should be read. Data are transferred once/day from the meter to the memory of the module.

The High Power RadioRouter module is equipped with two radio channels and detects automatically whether communication is High Power or Low Power. Channel 1 is typically used for communication between High Power radio network units, whereas channel 2 is used for collecting data from e.g. a battery supplied water meter.

This provides good stability and high security when transferring data.

The built-in router functionality provides you with the possibility of building up a radio network between the individual meters and the central RF Concentrator controlling the radio communications to and from the meters.

The High Power RadioRouter module is delivered with extra pulse inputs for water or electricity meters and with internal antenna and connection for external antenna.


Kamstrup's radio system is extremely robust to interference.



High Power RadioRouter module for MULTICAL® 602

DATA SHEET

Technical data



Electrical data

Supply	Supplied by the meter which must be mains supplied (High Power 24/230 VAC).
Range	
– channel 1 (High Power)	Urban areas up to 350 m Rural areas up to 5,000 m
– channel 2 (Low Power)	Up to 200 m
Frequency band	Is available for licence free and licence demanding frequencies: 434 MHz range (licence free) 444 MHz range (licence demanding)
Output power	500 mW on licence demanding frequencies (High Power) 10 mW on the licence free frequency (EU) (Low Power)
Reading period	Just one second for short data package containing billing data.

Mechanical data

Dimensions	45 x 90 mm
Ambient temperature	-40 - +60° C

Markings and approvals

MID	
CE marking	
EN 1434 approval	
R&TTE directive	EN 300 220 – class 2 EN 301 489

Ordering

Description

High Power RadioRouter module for MULTICAL® 602
– frequency codes

Type number

602008400003XX
318 CH
319 EU
327 SE2
328 SE
339 NO
348 DK2
349 DK
359 FI

External triangle antenna, with 2.5 meter antenna cable	6699 407
External triangle antenna, without antenna cable	6699 408
Converter box for external triangle antenna, without antenna cable	6699 417
Cavity wall antenna with 2.5 meter antenna cable	6699 442
Antenna cable for external triangle antenna, without antenna cable (50 meters)	6699 460